

## Hot Melt

Product Code	Basic Material	Viscosity	Application Temperature	Features	Application
HM1709EVH	EVA	950 ± 300 cps	150-160 °c	<ul style="list-style-type: none"> <li>• Cold Resistance: -15°c</li> <li>• Good Fluidity</li> <li>• High adhesive strength</li> <li>• Smokeless &amp; Odorless</li> </ul>	Bonding and lamination of various paper products, especially for Ice Cone Paper, non-woven fabrics, wood products, carton box packaging.
HM1711EVH	EVA	1100 ± 200 cps	150-160 °c	<ul style="list-style-type: none"> <li>• Good Fluidity</li> <li>• High adhesive strength</li> <li>• Smokeless &amp; Odorless</li> </ul>	To Stick Straw and Shrink Sleeve & other adhesive cladding, used for All kinds of paper products, non-woven fabric, wood products.
HM1711POH	Polyolefin Based	1100 ± 300 cps	150-160 °c	<ul style="list-style-type: none"> <li>• Good Fluidity</li> <li>• High adhesive strength</li> <li>• Smokeless &amp; Odorless</li> </ul>	Carton Box Package, for bonding and lamination of various paper products, non-woven fabrics, wood products.
HM1758PSH	Synthetic Resin Rubber	5800 ± 600 cps	150-160 °c	<ul style="list-style-type: none"> <li>• Pressure Sensitive</li> <li>• Adhesive</li> <li>• Light color</li> <li>• High bonding strength</li> <li>• Smokeless and odorless</li> </ul>	Paper Labeling, for the laminating paper, plastic, foam, PVC materials etc.

