

Over Print

Product Code	Components	Solvent	Printing Machine	Suitable for	Effect
OP6000PAT	One-component	Ethanol, Ethyl Acetate	Flexo & Gravure	- Polypropylene, Polyester, Polyethylene substrates - Snack foods and similar packaging applications	Excellent Matt effect, Paper touch
OP1006PAI	Two-component	MEK, PM, PMA	Gravure	Good scratch resistance	Paper Touch effect
OP1006ASI	Two-component	MEK, EA, PM	Gravure	- Good abrasion and scratch resistance - Good printability	High Gloss effect
OP1000HRI	One-component	Toluene, IPA, EAc	Gravure	- Excellent heat resistance and adhesion - Applicable to PTP product - Good abrasion and scratch resistance & Printability	High Gloss effect
OP1006PPI	Two-component	MEK, EA, PM	Gravure	- High Release property - Good abrasion and scratch resistance & Printability	High Gloss effect
OP1006PCI	Two-component	MEK, EA, PM	Gravure	- Good abrasion and scratch resistance - Good printability	High Gloss effect
OP1025HRM	Two-component	MEK For Resin Ethyl Acetate for Hardner	Gravure	- For coating printed or unprinted paper, plastic films and aluminum - Excellent slip coefficient with good rub and scratch resistance - Resists heat sealing up to 250°C	Excellent Gloss finish
MM1009MEI	Two-component Ethyl Acetate Based	MEK, DMC, PM, PMA	Gravure	- Good Scratch resistance, heat resistance - Good adhesion to PET, OPP - The degree of matt is easily controllable	Excellent Matt effect
OP1006STI	Two-component Water Based	Water: 70%	Dry Lamination Machine	- Good abrasion and scratch resistance - Good adhesion to PET	Velvet Touch, Soft Touch feel & Matt Effect

